CABLE SPECIFICATION

Sectional view:

Ground wire:9/0.18 Tinned copper stranding


Conductor:7/0.24 Tinned copper stranding

Core:Black, transparent; Black,red (HDPE)

Wrapping:AL foil (conductive layer facing outward)

Braiding:64/0.10 Tinned copper

Jacket:Grey(PVC-80P)



Coding content:

ALTEK KABEL 2PR 22AWG TWISTED SCREENED BRAIDED SHIELDED AUDIO & INSTRUMENTATION CABLE + Meter

	Model		8760 2P×22AWG+B	
	Conductor		7/0.24Tinned copper stranding	
	Maximum conductor resistance Ω / KM (20 $^{\circ}$ C)		62.57	
	ID		1.6±0.1mm	
	Core color		Black, transparent; Black,red	
	Insulation Materials		HDPE	
	Twisted pair		Black, transparent; Black,red	
	Each pair wrapping		Aluminum foil (conductive layer facing outward)	
	Synchronization completed	Stranding	Two pairs of twisted	
		Ground wire	9/0.18Tinned copper stranding	
	braiding		64/0.10Tinned copper	
	Jacket		Grey(PVC-80P)	
	OD		7.7±0.2mm	
	Sheath thickness		0.8mm	
	Rated vol	tage	300/300V	
d	Processing me		Cabling project, without processing	
	CHENZUEN	ATLUTONO	WITE 64 LIE	

9760 2DV22AMC LB

 Draw	Audit	Approved	scope	processing
			SHENZHEN HAILUTONG WIRE&CABLE CO.,LTD	

Customer Confirm: